

Approved Rim Contours

Radial Agricultural Drive Wheel Tires (R-1 thru R-4)

TIRE SIZE	RECOMMENDED RIM	APPROVED RIM
7.50R16	5.50F	5.50F, 5.00F, 5K, 6.00F, 4.00E, 6.00LB
7.50R18	5.50F	5.50F, 5.00F, 6.00F, 4.50E
9.5R24	W8	W8, W7, W8H
11.2R20	W9	W9, 9, W10
11.2R24	W10	W10, W10H, W9
12.4R20	W11	W11, 11, W9, 9, W10
12.4R24	W11	W11, W10, W10H
12.4R28	W11	W11, W10, W10H
12.4R32	W11	W11
13.6R24	W12	W12, W11
13.6R28	W12	W12, W11
13.9R36	W12	W12
13.6R38	W12	W12, DW12A, W11
14.9R24	W13	W13, W12
14.9R26	W12	W12, DW12A
14.9R28	W13	W13, W12
14.9R30	W13	W13, DW13A
14.9R34	W13	W13
14.9R46	W12A	W12A, W13A, DW13A
15.5R38	W14L	W14L
16.9R24	W15L	W15L
16.9R26	W15L	W15L, DW14A
16.9R28	W15L	W15L, W14L
16.9R30	W15L	W15L, W14L, DW15A
16.9R34	W15L	W15L, DW14A, W15A
16.9R38	W15L	W15L, W14L, DW14A, DW15A
16.9R46	W15L	W15L, W14L, DW14A
17.5LR24	W15L	W15L
18.4R26	DW16A	DW16A, W15L
18.4R30	DW16A	DW16A, W15L, DW15A
18.4R34	W16L	W16L, DW16A, W15L, W16A, W15A
18.4R38	W16A	W16A, DD16, W15L, W15A
18.4R42	W16A	W16A, DD16, DW16A
18.4R46	W16A	W16A, DD16, DW16A
19.5LR24	DW16L	DW16A, W16A
20.8R34	W18L	W18L, W16A, W18A
20.8R38	W18A	W18A, DW18A, DD18
20.8R42	W18A	W18A, DW18A, DD18
24.5R32	DW20A	DH21B, DW21B, DH21HB, DH21H, DH21, DW21A
23.1R26	DW20A	DW20B, DW20A
23.1R30	DH21B	DW20B, DW20A

TIRE SIZE	RECOMMENDED RIM	APPROVED RIM
28LR26	DW25B	DW25B, DW25A
30.5LR32	DH27B	DH27B, DW27B, DH27HB, DH27H, DW27A, DH27

*- Not Design Rim Width

IMPORTANT: Rim dimensions are standardized by the Tire and Rim Association for size and contour only, and particular tire and rim combinations are designated to assure proper mounting and fit of the tire to the rim. The load and cold inflation pressure imposed on the rim and wheel must not exceed the rim and wheel manufacturer's recommendations even though the tire may be approved for a higher load or inflation. Rims and wheels may be identified (stamped) with a maximum load and maximum cold inflation rating. For rims and wheels not so identified or for service conditions exceeding the rated capacities, consult the rim and wheel manufacturers to determine rim and wheel capacities for the intended service.

Approved Rim Contours

Bias Agricultural Drive Wheel Tires (R-1 thru R-4)

TIRE SIZE	RECOMMENDED RIM	APPROVED RIM
5-12	4JA	4JA
6-12	5JA	5JA
7-12	5JA	5JA
7-14	5JA	5JA, 5KB
7-16	6.00F	6L, 6.00F, 6LB
8-16	6.00F	6L, 6.00F, 6LB
12-16.5	9.75 15°	16.5x9.75 15°
7.2-16	6.00F	6.00F
7.2-30	W6	W6
8.3-16	W7	W7
8.3-24	W7	W7
9.5-16	W8	W8L, 8LB
9.5-20	W8	W8
9.5-24	W8	W7, W8, W8H
9.5-36	W8	W8
9.5-42	W8	W8, W9
11.2-16	W10L	W10L
11.2-24	W10H	W10, W10H, W9
11.2-28	W10H	W10, W10H, W9
11.2-34	W10	W10, W9
11.2-36	W9	W9
11.2-38	W10	W10
12.4-16	W10L	W10L, 10LB
12.4-24	W11	W11, W10, W10H
12.4-28	W11	W11, W10, W10H
12.4-36	W11	W11
12.4-38	DW11A	W11, DW11A, W10
12.4-42	W10	W10
13.6-16.1	W11C	16.1xW11C
13.6-16	W12L	W12L, W10L
13.6-24	W12L	W12, W11
13.6-26	DW12A	DW12A, W11, W12
13.6-28	W12	W12, W11
13.6-38	W12	W12, DW12A, W11
13.6-46	W12A	W12A
13.9-36	W12	W12
14.9-24	W13	W13, W12
14.9-26	W12	W12, DW12A
14.9-28	W13	W13, W12
14.9-30	W13	W13, DW13A
14.9-38	W13	W12, DW12A
15.5-38	W14L	W14L, DW14A
16.9-24	W15L	W15L
16.9-26	W15L	W15L, DW14A, DW15A
16.9-28	W15L	W15L, W14L

TIRE SIZE	RECOMMENDED RIM	APPROVED RIM
16.9-30	W15L	W15L, DW15A, W14L, DW14A
16.9-34	W15L	W15L, DW14A
16.9-38	W15L	W15L, W14L, DW14A, DW14, W15A
17.5L-24	W15L	W15L
18.4-16.1	W16C	16.1xW16C, 16.1xW16CH
18.4-24	W16L	W15L, W16L, W16A
18.4-26	DW16A	DW16A, W15L, DW15A
18.4-28	W16L	W16L, W15L, W16A
18.4-30	DW16A	DW16A, W15L, DW15A
18.4-34	W16L, DW16A	DW16A, W16L, W15L
18.4-38	W16A, DD16	W16A, DD16, W15L
18.4-42	W16A, DD16	W16A, DD16, DW16A
19.5L-24	W16L, DW16A	(8 & 10PR) W16L, DW16A, W15L
19.5L-24	DW16A	(12PR & higher) DW16A
20.8-34	W18L	W18L
20.8-38	W18A, DD18	W18A, DD18, DW18A
20.8-42	W18A, DD18	W18A, DD18, DW18A
21L-24	W18L, DW18A	(10PR) W18L, DW18A
21L-24	DW18A	(12 PR & higher) DW18A
21L-28	DW18A	(10PR) W18L, DW18A
21L-28	DW18A	(14PR) DW18L, DW18A
23.1-26	DW20B, DW20A	DW20B, DW20A
23.1-30	DW20B, DW20A	DW20B, DW20A
23.1-34	DW20B, DW20A	DW20B, DW20A
24.5-32	DW21A, DH21HB	DH21B, DW21B, DH21HB, DW20B, DW20A, DW21A, DH21, DH21H
28L-26	DW25B, DW25A	DW25B, DW25A
30.5L-32	DH27H, DW27B	(14PR & lower) DW27B, DH27, DH27H, DH27HB, DW27A
30.5L-32	DH27HB	(16PR & higher) DH27, DH27H, DH27B, DH27HB
VA30.5L-32 **	27VA	27VA
DH35.5L-32 **	DH31HB	DH31, DH31B, DH31H, DH31HB
VA35.5L-32 **	31VA	31VA

** VA and DH rims are not interchangeable

* – Not Design Rim Width

IMPORTANT: Rim dimensions are standardized by the Tire and Rim Association for size and contour only, and particular tire and rim combinations are designated to assure proper mounting and fit of the tire to the rim. The load and cold inflation pressure imposed on the rim and wheel must not exceed the rim and wheel manufacturer's recommendations even though the tire may be approved for a higher load or inflation. Rims and wheels may be identified (stamped) with a maximum load and maximum cold inflation rating. For rims and wheels not so identified or for service conditions exceeding the rated capacities, consult the rim and wheel manufacturers to determine rim and wheel capacities for the intended service.

Approved Rim Contours

Metric Size Agricultural Drive Wheel Tires (R1 thru R4)

TIRE SIZE	RECOMMENDED RIM	APPROVED RIM
200/70R16	W6	W6
230/95R32	W8	W8, W7
230/95R48	W8	W8
230/115R54	W8A	W8A
240/70R16	W8	W8, W9
250/80R16	W8	W8, W7, W9
250/80R18	W8	W8, W7, W9
250/95R34	W8	W8
250/90R38	W8	W8
250/90R48	W8	W8, W9
250/95R48	W8	W8, W9
250/95R50	W8	W8
250/95R54	W8H	W8H
260/70R16	W8	W8, W9
260/70R20	W8	W8, W9, 9
260/80R20	W8	W8
270/95R58	W8A	W8A
280/70R16	W9	W9, W10, W8
280/70R18	W9	W9, W10, W8
280/70R20	W9	W9, W10, W8
290/95R34	W10	W10
290/90R38	W9	W10
290/90R42	W9	W9, W10
290/95R34	W10	W10, W9
300/70R20	W9	W9, W10
300/90R50	W9	W9, W10, W11
320/70R24	W10	W10, W11
320/75R24	W10	W10, W11
320/80R42	W10	W10
320/85R24	W11	W11, W9, W10, W10H
320/85R34	W10L	W10H
320/85R38	W10	W10, W11, DW10A, DW11A
320/80R42	W9	W9, W10
320/90R42	W10	W10, W9
320/90R46	W10A	W10A, DW10A
320/90R50	W10A	W10A, DW10A
320/90R54	W10A	W10A
320/105R54	W10A	W10A
320/90R72.5	72.5x10.00LSW 15°	72.5x10.00LSW 15°
340/80R18	W9	W9, W11
340/85R46	W12A	W12A, DW10A, W10A
340/90R28	W11	W11
360/70R20	W11	W11, W10, W12
360/70R24	W11	W11, W10, W12
360/70R28	W11	W11, W10, W12
380/70R20	W12	W12, W11, W13
380/70R24	W12	W12, W11, W13
380/70R28	W12	W12, W11, W13
380/80R38	W11	W12
380/80R42	W12	W12, DW12A, W11, DW11A
380/85R24	W12	W12, W11, W13
380/85R28	W12	W12, W11, W13
380/85R30	W12	W12, W13, DW13A
380/85R34	W12	W12, W13
380/80R38	W12	W12, DW12A
380/95R38	W12	W12, DW12A
380/85R46	W13A	W13A, DW13A, W12A
380/90R46	W12A	W12A, W13A, DW13A
380/90R50	W12A	W12A, DW12A
380/90R54	W12A	W12A
380/105R50	W13A	W12A, W13A, DW13A, DW12A
385/85R34MPT	W12	W12, DW12, W13, DW13
400/70R18	W13	W14L, 13

TIRE SIZE	RECOMMENDED RIM	APPROVED RIM
400/70R18IND	W13	W12, W13
400/70R20	W13	W14L, 13
400/70R20IND	W13	W14L, W12, W13
420/70-24	W13	W13, W12, W14L
420/70R24	W13	W13, W12, W14L
420/70R28	W13	W13, W12, W14L
420/80R46	W13A	W13A, DW13A, W12A
420/85R26	W13	W13, DW13A
420/90R30	W13	W13, DW13A, W14L, W15L
420/85R28	W13	W12, W13, W14L
420/85R38	W15L	W15L, W14L, W15A
420/85R34	W13	W13, W14L, DW14A, W15A, W15L
420/80R46	W13A	W13A, DW13A, W12A
420/90R30	W13	W13, DW13A, W14L
440/80R28	W15L	W15L, W14L, W13L
460/70R24	W14L	W14L, W15L
460/85R30	W16L	W16L, W15L, W14L
460/85R42	W16L	W16L, W15L, W14L
480/65R28	W15L	W15L, W14L
480/70R24	W15L	W15L, W16L, W14L
480/70R28	W15L	W15L, W14L, W16L
480/70R30	W15L	W15L, W14L, W16L, DW15A, W16A
480/70R34	W15L	W15L, W16L, W15A, W16A, DW16A
480/80R24	W15L	W15L, W16L, W18L
480/80R26	DW15A	DW15A, W15L, W16L
480/80R30	W15L	W15L, W14L, W16L, DW15A
480/80R34	W16L	W16L, DW16A, W15L
480/80R38	W15L	W15L, W15A, W16A, DD16, DW16A
480/80R42	W16A	W16A, DW16A, DD16
480/80R46	W16A	W16A, DW16A, DD16
480/80R50	DW15A	DW15A, W15A, DW16A
480/85R26	W15L	DW15A, W15L, W16L
480/85R30	W15L	W15L, W16L, DW15A
480/85R34	W15L	W15L, W16L, W16A, DW14A, DW16A, W15A
480/95R50	W15A	DW15A, W15A, DW16A
500/60-22.5	AG16.00	AG16.00
500/65D24	W16L	W16L, W16A, W15L, DW16A
500/70R24	W16L	W16L, W16A, W15L, DW16A
500/70R24IND	W16L	W16L, W16A, W15L, DW16A
500/85R24	W16L	W16L, W16A, W15L, DW16A
VA500/95D32	13.00VA	13.00VA
520/70R30	W16L	W16L, W18L
520/70R38	W16L	W16L, W16A, DD16, W18A, DD18, W15L, W15A
520/85R38	W16A	W16A, DD18, W18A, DD16, DW16A, DW18A
520/85R42	W16A	W16A, W18A, DW18A, DW16A, DD16, DD18
520/85R46	W16A	W16A, W18A, W16L, W18L, DD16
540/65R24	W16L	W16L, W18L
540/65R30	W16L	W16L, W16A, DW16A
540/65R34	W16L	W16L, W18L, W16A, W18A
540/70R24	W16L	W16L, W18L
540/75R28	W18L	W18L, W16L
540/75R34	W18L	W18L, W16L
580/70R24	W18L	W18L
580/70R26	DW18L	DW18L, W18L
580/70R38	W18L	W18A, DW18A, DD18
600/50D22.5	AG20.00	AG20.00
600/60R34	DW20A	DW20A, MW20A, DW20B, MW20B
600/65R28	W18L	W18L
600/70R28	W18L	W18L, DW20B, DW18L
600/70R30	W18L	DW20B, DW20A, DW18A
620/75R26	DW20A	DW20B, DW20A
620/75R30	DW20A	DW20B, DW21B, DW21A, DW20A

TIRE SIZE	RECOMMENDED RIM	APPROVED RIM
620/70R42	DW20A	DW20B, MW20B, DW20A, MW20A
620/70R46	DW20A	DW20B, MW20B, DW20A, MW20A
650/75R32	DW21A	DW21B, DH21B, DH21H, DH21HB, DW21A, DH21
650/75R34	DW20A	DW20B, DW21B, DW20A, DW21A
650/75R38	DW21A	DW21B, DW23B, DW20A, DW21A, DW23A
650/85R38	DW20A	DW20B, MW23B, DW20A, MW23A
650/65R38	DW20A	DW20B, DW20A
650/65R42	DW20A	DW23B, MW23B, MW23A, DW23A
710/70R38	MW25A	MW25B, DW25B
710/70R42	MW25A	MW25B, DW25B
750/55R26	DW25A	DW25B, DW25A
750/65R26	DW25A	DW25B, DW25A
800/65R32	DW27A	DH27HB, DH27H, DH27, DH27B, DW27B
800/70R38	DW27A	DW27B, MW28B
850/80R38	DW27A	DW27B, MW28B, DW27A, MW28A
850/75R42	DW27B	DW27B, MW28B, DW27A, MW28A
900/50R32	DW31A	DW30B, DH31B, DH31HB, DH31H, DW31B, DW30A, DW31A, DH31
900/50R42	DW31A	DW30B, DW31B, MW30B, MW30A, DW30A, DW31A
900/55R32	DW31A	DW30B, DH31B, DH31HB, DH31H, DW31B, DW30A, DW31A, DH31
900/60R32	DW31A	DW30B, DH31B, DH31HB, DH31H, DW31B, DW30A, DW31A, DH31
900/65R32	DW31A	DW30B, DH31B, DH31HB, DH31H, DW31B, DW30A, DW31A, DH31
900/55R42	DW31A	DW30B, DW31B, MW30B, MW30A, DW30A, DW31A
900/60R42	DW31A	DW30B, DW31B, MW30B, MW30A, DW30A, DW31A
900/65R32	DW30A	DW30B, DH31B, DH31HB, DH31H, DW31B, DW30A, DW31A, DH31
900/75R32	DW30B	DW30B, DH31B, DH31HB, DH31H, DW31B, DW30A, DW31A, DH31
1100/45R46	DW36HB	DW36HB
1050/50R32	DW36B	36.0VA, DW36B, 36DWM, DH36H, DH36HB, DW36A
1000/50R25	36.0TH	36.0TH
1250/50R32	DW44B	DW44B
1250/35R42	DW44B	DW44B
LSW1100R46	LSW38.0	LSW38.0
LSW430R38	W15L	W14L, W15L, DW14A, DW15A
LSW525R50	DW16A	DW16A

Metric Size Agricultural Implement Tires

TIRE SIZE	RECOMMENDED RIM	NO APPROVED RIM
340/60R16.5	11	
340/65R18	W11	
360/65R17.5	10.5	
380/55R16.5	12	
380/60R16.5	12	
420/55R22.5	13	
440/55R18	W14	
480/55R22.5	15	

IMPORTANT: Rim dimensions are standardized by the Tire and Rim Association for size and contour only, and particular tire and rim combinations are designated to assure proper mounting and fit of the tire to the rim. The load and cold inflation pressure imposed on the rim and wheel must not exceed the rim and wheel manufacturer's recommendations even though the tire may be approved for a higher load or inflation. Rims and wheels may be identified (stamped) with a maximum load and maximum cold inflation rating. For rims and wheels not so identified or for service conditions exceeding the rated capacities, consult the rim and wheel manufacturers to determine rim and wheel capacities for the intended service.

Terra-Tire® High Flotation Tires

TIRE SIZE	RIM RECOMMENDED	ALTERNATE RIM
27 x 8.50-15 NHS	7JA	7.00 I-55, I-70, I-90
27 x 9.50-15 NHS	7JA	8LB
25 x 7.50-15 NHS	6LB	
25 x 10.50-15 NHS	8LB	
25 x 12.50-15 NHS	10LB	
27x10.50-15 NHS	8LB	
29x10.50-15 NHS	8LB	
29x12.50-15 NHS	10LB	
29x14.00-15 NHS	10LB	12LB
31 x 12.50-15 NHS	10LB	
31 x 13.50-15 NHS	10LB	
31 x 15.50-15 NHS	13LB	
33 x 12.50-15 NHS	10LB	
33 x 14.50-15 NHS	10LB	
36 x 13.50-15 NHS	10LB	
33x12.50-16.5 NHS	9.75	
35x12.00-16.5 NHS	9.75	
35x19.00-16.1 NHS	W16C	W16CH
38 x 20.00-16.1 NHS	W16C	W16CH
38 x 14.00-20 NHS	W11H	
38x18.00-20 NHS	W14L	W14LH
41 x 14.00-20 NHS	W11H	
42 x 25.00-20 NHS	20.50VF	20.50HF
44 x 18.00-20 NHS	W14L	W14LH
44 x 41.00-20 NHS	36.0VF	
48 x 25.00-20 NHS	20.50VF	20.50HF
48 x 31.00-20 NHS	26.00VF	26.00HF
66 x 43.00-25 NHS	36.0TH	See Notes
66 x 44.00-25 NHS	36.0TH	See Notes
67 x 34.00-25 NHS	30.0TH	See Notes
54 x 31.00-26 NHS	DW25A	DW26A
67 x 34.00-26 NHS	DW30	
67 x 34.00-30 NHS	DW30	
68x50.00-32 NHS	DW44A	44DWM, DH44, DH44H
VA73 x 44.00-32 NHS	36.0VA	
DH73 x 44.00-32 NHS	DH36	

Flange Requirements for 25" Diameter Rim High Flotation Tires

Notes:

- Proper bead fit on the rim is important for optimum tire performance and tire life especially for tires that are subjected to high deflections as encountered in variable load operations with spreader trucks and combines.
- All 25" bead diameter Terra-Tire tires fit the "TH" rim with 1.5" flange height., with the exception of 20 PR tires. (See Note 3 below.) The 1.5" flange height rim provides optimum tire performance under all service conditions including the more severe service in variable load operations. Only the "TH" rim with 1.5" flange height should be used for the Goodyear Terra-Tire tires which require the 25" rim diameter.
- Caution must be exercised in selecting the correct rim for 20 PR tires. There are two versions of 20 PR flotation tires. One uses the 1.5" flange height and the other uses a 2.5" flange height rim. Use only the correct tire and rim combinations for proper tire-to-rim fit.

Approved Rim Contours

Terra-Tire® Small Flotation Tires and Utility Vehicle Tires

TIRE SIZE	RIM RECOMMENDED	ALTERNATE RIM
11x4.00-5 NHS	3.00A	
13x5.00-6 NHS	3.50A	
13x6.50-6 NHS	5.375 I-55, I-70, I-90	
15x6.00-6 NHS	4.50A	
15x6.50-6 NHS	5.375 I-55, I-70, I-90	
16x6.50-8 NHS	5.375 I-55, I-70, I-90	
16x7.50-8 NHS	5.375 I-55, I-70, I-90	
18x6.50-8 NHS	5.375 I-55, I-70, I-90	
18x7.00-8 NHS	5.50 I-55, I-70, I-90	
18x7.00-10 NHS	5.50 I-55, I-70, I-90	
18x8.50-8 NHS	7.00 I-55, I-70, I-90	
18x8.50-10 NHS	7.00 I-55, I-70, I-90	
18x9.50-8 NHS	7.00 I-55, I-70, I-90	
18x10.50-8 NHS	7.00 I-55, I-70, I-90	8.00 I-55, I-70, I-90
18x10.50-10 NHS	7.00 I-55, I-70, I-90	8.00 I-55, I-70, I-90
20x8.00-8 NHS	7.00 I-55, I-70, I-90	
20x8.00-10 NHS	7.00 I-55, I-70, I-90	6JA
20x10.00-8 NHS	7.00 I-55, I-70, I-90	8.00 I-55, I-70, I-90
20x10.00-10 NHS	7.00 I-55, I-70, I-90	8.00 I-55, I-70, I-90
20x12.00-10 NHS	8.50 I-55, I-70, I-90	10.50 I-55, I-70, I-90
21x8.00-10 NHS	7.00 I-55, I-70, I-90	
21x10.00-10 NHS	7.00 I-55, I-70, I-90	8.00 I-55, I-70, I-90

TIRE SIZE	RIM RECOMMENDED	ALTERNATE RIM
21x11.00-8 NHS	7.00 I-55, I-70, I-90	8.50 I-55, I-70, I-90
21x11.00-10 NHS	7.00 I-55, I-70, I-90	8.50 I-55, I-70, I-90
22x11.00-8 NHS	8.50 I-55, I-70, I-90	10.50 I-55, I-70, I-90
22.5x10.00-8 NHS	7.00 I-55, I-70, I-90	8.00 I-55, I-70, I-90
23x8.50-12 NHS	7.00 I-55, I-70, I-90	7JA
23x8.50-14 NHS	7.00 I-55, I-70, I-90	7JA
23x9.00-12 NHS	7.00 I-55, I-70, I-90	7JA
23x9.50-12 NHS	7.00 I-55, I-70, I-90	7JA, 8.50 I-55, I-70, I-90, 81/2JA
23x10.50-12 NHS	7.00 I-55, I-70, I-90	8.00 I-55, I-70, I-90
24x8.50-14 NHS	7.00 I-55, I-70, I-90	7JA
24x11.00-10 NHS	8.50 I-55, I-70, I-90	
24x12.00-12 NHS	8.50 I-55, I-70, I-90	10.50 I-55, I-70, I-90
24x13.00-12 NHS	9_JA	10_JA
25x7.50-15 NHS	6LB	
25x8.50-14 NHS	7.00 I-55, I-70, I-90	7JA
25x12.00-9 NHS	8.50 I-55, I-70, I-90	
25x12.50-9 NHS	10LB	
26x10.50-12 NHS	7 I-55, I-70, I-90	8.00 I-55, I-70, I-90
26x12.00-12 NHS	8.50 I-55, I-70, I-90	10.50 I-55, I-70, I-90, 8_JA, 9_JA, 10_JA
26x14.00-12 NHS	10_JA	
26.5x14.00-12 NHS	10_JA	

Agricultural Steering Wheel Tractor Tires

SIZE	RECOMMENDED RIM	ALTERNATE RIM
4.00-12 SL	3.00D	2.50C
4.00-15 SL	3.00D	
4.00-19 SL	3.00D	
5.00-15 SL	3.00D	4J
5.50-16 SL	4.00E	4.25KA, 4.50E
6.00-14 SL	5KB	
6.00-16 SL	4.00E	4.25KA, 4.50E
6.50-16 SL	4.50E	4.00E, 4.25KA, 5.50F
7.50-16 SL	5.50F	6LB
7.50-18 SL	5.50F	
7.50-20 SL	5.50F	6LB
8.00-16 SL	5.50F	
9.00-10 NHS	6.00F (2Piece)	5.50F (2 Piece)
9.50-20 SL	W7L	

SIZE	RECOMMENDED RIM	ALTERNATE RIM
9.50-24 SL	W8	W8H
10.00-16 SL	W8L	8LB
11.00-16 SL	W8L	8LB, W10L, 10LB
11.00-20 SL	W10H	
11.00-24 SL	W10	W10H
12.4-30	W12	W11
7.5L-15 SL	6LB	5KB
9.5L-15 SL	8LB	
11L-15 SL	8LB	10LB
11L-16 SL	W8L	8LB, W10L, 10LB
14L-16.1 SL	16.1xW11C	
16.5L-16.1 SL	16.1xW14C	16.1xW14CH
14.5/75L-16.1 SL	16.1xW11C	

LSW Tires on 11° LSW Rims

SIZE	RECOMMENDED RIM	SIZE	RECOMMENDED RIM
LSW165-241	241x137LSW	LSW385-648	648x317LSW
LSW265-343	343x229LSW	LSW395-851	851x317LSW
LSW265-521	521x210LSW	LSW400-648	648x356LSW
LSW305-521	521x210LSW	LSW420-648	648x356LSW
LSW305-546	546x248LSW	LSW455-610	24xW15L
LSW305R343	343x229LSW	LSW455-610	24xW15L
LSW320-597	597x267LSW	LSW525R1257	1257x457LSW
LSW330-851	851x254LSW	LSW570-648	648x457LSW
LSW350-597	597x267LSW	LSW610R470	470x483LSW
LSW360-851	851x254LSW	LSW900R965	38xDH31H
LSW375-851	851x305LSW	LSW1100R1181	1181x483LSW
LSW375R1410	1410x305LSW		

LSW Tires on 5° LSW Rims

Size	Recommended Rim
LSW252R50	W8
LSW430R38	W15L
LSW495-762*	30xDW15A
LSW525R50	50xDW18A
LSW585R34	DW20A
LSW900R965	38xDH31H
LSW1100/45R46	46xW38A

*Will be converted to LSW495R30

Agricultural Implement Tires (I-1 Thru I-3)

SIZE	RECOMMENDED RIM	ALTERNATE RIM
4.00-9 SL	3.00D	
4.00-12 SL	3.00D	2.50C
4.00-12 NHS	3.00D	2.50C
4.00-15 SL	3.00D	
4.00-18 SL	3.00D	
5.00-15 SL	3.00D	4J
5.50-16 SL	4.00E	4.25KA, 4.50E
5.90-15 SL	4_KB	4J, 5KB
6.00-16 SL	4.00E	4.25KA, 4.50E
6.40-15 SL	4_KB	4J, 5KB
6.50-16 SL	4.50E	4.00E, 4.25KA
6.70-15 SL	4_KB	5KB
7.50-10 SL	5.50F	6.00F
7.50-14 SL	5KB	6KB
7.50-16 SL	5.50F	6LB
7.50-18 SL	5.50F	
7.50-20 SL	5.50F	
7.50-24 SL	W7	
7.60-15 SL	6LB	6L
9.00-10 SL	5.50F	6.00F
9.00-10 NHS	6.00F (2Piece)	5.50F (2 Piece)
9.00-16 SL	6LB	W8L, 8LB
9.00-24 SL (6PR)	W7	W8, W8H
9.00-24 SL (8PR)	W8H	
10.00-15 SL	8LB	
11.25-24 SL	W10	W10H, W8, W8H
11.25-28 SL	W10	W10H
13.50-16.1 SL	16.1xW11C	
8.5L-14 SL	6KB	8KB
9.5L-14 SL	8KB	
9.5L-15 SL	8KB	
11L-14 SL	8KB	

SIZE	RECOMMENDED RIM	ALTERNATE RIM
11L-15 SL	8LB	10LB
11L-16 SL	W8L	8LB, W10L, 10LB
12.5L-15 SL	10LB	
12.5L-16 SL	W10L	10LB
14L-16.1 SL	16.1xW11C	
16.5L-16.1 SL	16.1xW14C	16.1xW14CH
19L-16.1 SL	16.1xW16C	16.1xW16CH
21.5L-16.1 SL (14PR and Down)	16.1xW18C	16.1xW16C, 16.1xW18CH, 16.1xW16CH
21.5L-16.1 SL (18PR)	16.1xW18CH	
22.5LL-16.1	16.1xW18C	

Highway Approved Agricultural Implement Tires (FI)

Size	Recommended Rim	Alternate Rim
9.5L-15FI	8LB	
10.0-15FI	8LB	
11L-15FI	8LB	81/2J, W8L, 8J, 10LB
12.5L-15FI	10LB	
13.50-15FI	10J	11J
14L-16.1FI	16.1xW11C	
16.5L-16.1FI	16.1xW14C	16.1xW14CH
21.5L-16.1FI	16.1xW18C	16.1xW18CH, 16.1xW16C, 16.1xW16CH

IMPORTANT: Rim dimensions are standardized by the Tire and Rim Association for size and contour only, and particular tire and rim combinations are designated to assure proper mounting and fit of the tire to the rim. The load and cold inflation pressure imposed on the rim and wheel must not exceed the rim and wheel manufacturer's recommendations even though the tire may be approved for a higher load or inflation. Rims and wheels may be identified (stamped) with a maximum load and maximum cold inflation rating. For rims and wheels not so identified or for service conditions exceeding the rated capabilities, consult the rim and wheel manufacturers to determine rim and wheel capacities for the intended service.

Approved Rim Contours

Miscellaneous Agricultural Service Tires

Size	Recommended Rim	Alternate Rim
8.00-16 SL	5JA	
13.6-16 NHS	W12	
205/50-10 NHS	6 I-55, I-70, I-90	7 I-55, I-70, I-90, 6JA
3.50-6 NHS	3.25A	
4.10-4 NHS	3.25A	
4.10-6 NHS	3.25A	
4.10/3.50-6 NHS	3.25A	
4.80-8 NHS	3.75 I-55, I-70, I-90	
8.00-6 NHS	7 I-55	
21.5L-16.1	16.1xW18C	16.1xW18CH, 16.1xW16C, 16.1xW16CH
10.5/80-18	W9	W8, 9
12.5/80-18	W9	11
10.5-20MPT	W9	

Size	Recommended Rim	Alternate Rim
12.5-20MPT	W10L	
15.5/80-24	W12	W13, W14L
16.0/70-20	12SDC	13, 13SDC, 14
20.5x5.5-12	4JA	
19.5/60-26	W16L	
23.5/55R26	DW20A	DW20B
23.5/55-26	DW20A	DW20B
26/6.50-15	41/2KB	41/2K
26/7.75-15	5KB	
25x10.5LL-15 NHS	8LB	
27X12LL-15 NHS	10LB	
400/70-20	W14L	14, 13, 13SDC
480/45-17	16.00	

Highway Tires (FI shown with Implements)

Size	Recommended Rim	Alternate Rim
7.00-16LT	5K	5_K, 6L, 6K
9.00-16LT	6.50H	
9.00-20	6.5	7, 7.5, 7.5VM
10.00-20	7	7.5, 8, 7.5VM
11.00-20	7.5	8, 8.5, 8.5VM
36x12.5-16.5LT	9.75	8.25
ST155/80*13	4_JB	5JB
ST165/80*13	4_JB	5JB
ST175/80*13	4_JB	5JB, 5_JB
ST185/80*13	4_JB	5JB, 5_JB, 6JB
ST195/75*14	5J	5_J, 6J
ST205/75*14	5J	5_J, 6J, 6_J
ST215/75*14	5_J	6J, 6_J, 7J
ST205/75*15	5J	5_J, 6J, 6_J
ST225/75*15	6J	6_J, 7J
ST235/75*15	6J	6_J, 7J, 71/2J
ST215/75*16	5.50F	5_J, 5_K, 5_KB, 6J, 6K, 6L, 6_J, 6_K, 6_L, 7J, 7K, 7KB, 7L
ST235/80*16	6J	6K, 6L, 6_J, 6_K, 6_L, 7J, 7K, 7KB, 7L, 7_J

Size	Load Range	Recommended Rim	Alternate Rim
4.80-8	A & B:	3.75 I-55, I-70	
	C:	3.75 I-70	
4.80-12	B:	3.75 I-55, I-70	4.00 I-55, I-70, I-90, 4JA
	C:	3.75 I-70	4.00 I-70, I-90, 4JA
5.30-12	B:	4.00 I-55, I-70, I-90	4.25 I-55, I-70, I-90, 4JA
	C:	4.00 I-70, I-90	4.25 I-70, I-90, 4JA
5.70-8	B:	3.75 I-55, I-70	4.50 I-55, I-70, I-90
	C:	3.75 I-70	4.50 I-70, I-90
6.90-9	A & B:	4.50 I-55, I-70, I-90	4.50K, 5.50K 4.25 I-55, I-70, I-90
	C:	4.50 I-70, I-90	4.50K, 5.50K 4.25 I-70, I-90
6.90-9	D & E:	4.50 I-90	4.50K, 5.50K 4.25 I-90
	C & E:	5.00F	5.50F
7.50-10	E:	5.50F	6 I-70, I-90, 6JA
16.5x6.5-8	A & B:	5.375 I-55, I-70, I-90	
	C:	5.375 I-70, I-90	
20.5x8.0-10	D:	5.375 I-90	
	B:	6.00 I-55, I-70, I-90	6JA
18.5x6.5-8	C, D & E:	6.00 I-70, I-90	6JA
	B:	5.375 I-55, I-70, I-90	
18.5x8.5-8	C:	5.375 I-70, I-90	
	B:	7.00 I-55, I-70, I-90	
205/50*10	C:	7.00 I-70, I-90	
	A & B:	7.00 I-55, I-70, I-90	6.00 I-55, I-70, I-90

Approved Rim Contours

ATV Tires

Size	Approved Rim
AT18x9.5-8	7.5AT, 8.0AT, 8.5AT
AT18x11-8	8.5AT, 9.0AT
AT20x7-8	5.5AT, 6.0AT
AT20x10-8	7.5AT, 8.0AT, 8.5AT
AT20x11-8	8.5AT, 9.0AT
AT21x12-8	9.0AT, 9.5AT, 10.0AT
AT21x12.5-8	9.0AT, 9.5AT, 10.0AT
AT22.5x10-8	7.5AT, 8.0AT, 8.5AT
AT22x11-8	8.5AT, 9.0AT
AT22x12-8	9.0AT, 9.5AT, 10.0AT
AT22x12.5-8	9.0AT, 9.5AT, 10.0AT
AT20x10-9	7.5AT, 8.0AT, 8.5AT
AT20x11-9	8.5AT, 9.0AT
AT21x7-9	5.5AT, 6.0AT
AT21x8-9	6.0AT, 6.5AT
AT21x12.5-9	9.0AT, 9.5AT, 10.0AT
AT22x11-9	8.5AT, 9.0AT
AT22x12-9	9.0AT, 9.5AT, 10.0AT
AT22x12.5-9	9.0AT, 9.5AT, 10.0AT
AT25x12-9	9.0AT, 9.5AT, 10.0AT
AT25x13-9	10.0AT, 10.5AT
AT25x13.5-9	10.0AT, 10.5AT
AT18x11-10	8.5AT, 9.0AT
AT20x10-10	7.5AT, 8.0AT, 8.5AT

Size	Approved Rim
AT20x11-10	8.5AT, 9.0AT
AT21x7-10	5.5AT, 6.0AT
AT21x12.5-10	9.0AT, 9.5AT, 10.0AT
AT22x7-10	5.5AT, 6.0AT
AT22x8-10	6.0AT, 6.5AT
AT22x11-10	8.5AT, 9.0AT
AT22x12-10	9.0AT, 9.5AT, 10.0AT
AT22x12.5-10	9.0AT, 9.5AT, 10.0AT
AT23x7-10	5.5AT, 6.0AT
AT23x8-10	6.0AT, 6.5AT
AT23x10-10	7.5AT, 8.0AT, 8.5AT
AT24x10.5-10	7.5AT, 8.0AT, 8.5AT
AT24x11-10	8.5AT, 9.0AT
AT24x11.5-10	8.5AT, 9.0AT
AT24x12-10	9.0AT, 9.5AT, 10.0AT
AT25x9.5-10	7.5AT, 8.0AT, 8.5AT
AT25x11-10	8.5AT, 9.0AT
AT25x12-10	9.0AT, 9.5AT, 10.0AT
AT25x13.5-10	10.0AT, 10.5AT
AT23x8-11	6.0AT, 6.5AT
AT24x8-11	6.0AT, 6.5AT
AT24x9-11	7.0AT, 7.5AT
AT24x10-11	7.5AT, 8.0AT, 8.5AT
AT25x8-11	6.0AT, 6.5AT

Size	Approved Rim
AT25x9.5-11	7.5AT, 8.0AT, 8.5AT
AT25x10-11	7.5AT, 8.0AT, 8.5AT
AT25x12.5-11	9.0AT, 9.5AT, 10.0AT
AT23x8-12	6.0AT, 6.5AT
AT23x10-12	7.5AT, 8.0AT, 8.5AT
AT24x8-12	6.0AT, 6.5AT
AT24x9-12	7.0AT, 7.5AT
AT24x11-12	8.5AT, 9.0AT
AT25x8-12	6.0AT, 6.5AT
AT25x9.5-12	7.5AT, 8.0AT, 8.5AT
AT25x10-12	7.5AT, 8.0AT, 8.5AT
AT25x11-12	8.5AT, 9.0AT
AT25x12.5-12	9.0AT, 9.5AT, 10.0AT
AT26x9-12	7.0AT, 7.5AT
AT26x10-12	7.5AT, 8.0AT, 8.5AT
AT26x10.5-12	7.5AT, 8.0AT, 8.5AT
AT26x12-12	9.0AT, 9.5AT, 10.0AT
AT27x9-12	7.0AT, 7.5AT
AT27x11-12	8.0AT, 8.5AT, 9.0AT
AT28x9-12	6.5AT, 7.0AT, 7.5AT
AT28x11-12	8.0AT, 8.5AT, 9.0AT
LSW230-394	AT394x152LSW
LSW255-394	AT394x152LSW

Tires in Skid Steer Service

Size	Approved Rim
20x8.00-10 NHS	6.00E, 7.00E, 7.00I
23x8.50-12 SS	7.00-I, 7JA
23x8.50-12 NHS	7.00-I, 7JA
23x8.50-14 SS	7.00-I, 7JA, 7KB
23x8.50-14 NHS	7.00-I, 7JA, 7KB
26X12.00-12 SS	8.5-I, 10.5-I, 8_JA, 9_JA, 10_JA
26X12.00-12 NHS	8.5-I, 10.5-I, 8_JA, 9_JA, 10_JA
25x8.50-14 SS	7.00-I, 7JA, 7KB
27x8.50-15 NHS	7JA
27x10.50-15 NHS	8LB
28X8.50-15 NHS	7JA
30.5x12.50-16.5 NHS	9.75
31x15.50-16.5 NHS	12.00
33x14.50-16.5 NHS	12.00
33x15.50-16.5 NHS	12.00
43x16.00-20 NHS	W14L, W14LH

Size	Approved Rim
5.70-12 NHS	4.50-I, 5JA
7.00-15 SS	5.50F
7.00-15 NHS	5.50F
8.25-15 SS	6LB
8.25-15 NHS	6LB
10-16.5 NHS	8.25
12-16.5 NHS	9.75
14-17.5 NHS	10.5
15-19.5 NHS	11.75, 12.25
10.5/80-18	W9, W8, 9
12.5/80-18	W9, 11
250-15 NHS	7, 9
300-15 NHS	9
LSW320-597	597x267LSW (Replaces 12.5/80-18)

Size	Approved Rim
LSW265-521	521x210LSW (Replaces 10-16.5 NHS)
LSW305-546	546x248LSW (Replaces 12-16.5 NHS)
LSW350-597	597x267LSW (Replaces 14-17.5 NHS)
LSW385-648	648x317LSW (Replaces 15-19.5 NHS)